

F  
I  
L  
L  
Z  
Y  
M  
  
A  
3

Cleaning product for the maintenance of membrane filters

Powerful cleaning	Industrial cleaning	CIP	Performance
----------------------	------------------------	-----	-------------

**Application**                      **Powerful cleaning product recommended for the unblocking of installations of membrane separation.**  
 → Concentrated formulation in dispersal agents ;  
 → Formulation specifically adapted for fouling with oil origin ( Mineral oil, naphta, gazoil, ...)

**Use**                                      Installation of membrane separation.

**Dosage / Instructions**                      from 0,5 to 1,5 %  
**Closed circuits – CIP :**  
 → Prepare a solution with recommended dosage and let circulate during 20 to 40 minutes at a temperature of 60°C.  
 → Rinse the installation.

**Active Matters**                      **Among others :**

Solvent
Surfactants

**Physical-Chemical Properties**

<b>Aspect</b>	Liquid
<b>pH</b>	7±0,5
<b>Volume massa</b>	0,940±0,050 kg/l

**25/03/2010**  
**S.A. REALCO N.V.**

F

I

L

Z

Y

M

A

3

**Précautions**

Product developed for professional use only. It is recommended to use the product for the applications defined here above.

For more information on our product, we invite you to consult the safety data sheet that can be provided to you on a simple request.



**Article code  
Packaging  
Palettization**

LIQ0982  
1 x 10 L  
60 cans / pallet

LIQ0971  
1 x 25 L  
24 cans / pallet

**Storage**

Storage in the packing of origin closed, between +4°C and +25°C.

25/03/2010  
S.A. REALCO N.V.

Parc scientifique • Wetenschappelijk park • Avenue Albert Einsteinlaan, 15 • B-1348 Louvain-la-Neuve (Belgium)

Tel. +32 (0)10/45.30.00 • Fax +32 (0)10/45.63.63 • info@realco.be • www.realco.be

TVA/BTW-BE-0444.458.750•RPM/RPR Nivelles•ING-350-01322306-20